



## KILAVUZ KONVEYÖR BANT VE KAYIŞ SİSTEMLERİ SAN.VE TİC. LTD ŞTİ.

Model	Mesh boyutu	Malzeme	Kalınlık	Ağırlık	Temp Direnç	Max Genişlik	Gerilme direnci
KT-22	2x2mm	fiberglas	0.7mm	450g / m <sup>2</sup>	-70 ~ 320 °C	4000mm	350/310N/cm
KT-44	4x4mm	fiberglas	1.0mm	400g / m <sup>2</sup>	-70 ~ 320 °C	4000mm	390/320N/cm
KT-46	4x4mm	fiberglas	1.0mm	500g / m <sup>2</sup>	-70 ~ 320 °C	4000mm	395/370N/cm
KT-66	6x6mm	fiberglas	1.2mm	450g / m <sup>2</sup>	-70 ~ 320 °C	4000mm	360/300N/cm
KT-1010	10x10mm	fiberglas	1.2mm	450g / m <sup>2</sup>	-70 ~ 320 °C	4000mm	360/300N/cm
KT-22A	2x2mm	fiberglas	0.7mm	450g / m <sup>2</sup>	-70 ~ 320 °C	4000mm	350/310N/cm
KT-44A	4x4mm	fiberglas	1.0mm	400g / m <sup>2</sup>	-70 ~ 320 °C	4000mm	390/320N/cm
KT-55GK	5x5mm	fiberglas+ Kevlar	1.2mm	600g / m <sup>2</sup>	-70 ~ 320 °C	4000mm	895/370N/cm
KT-44K	4x4mm	Kevlar	1.0mm	500g / m <sup>2</sup>	-70 ~ 320 °C	4000mm	900/600N/cm
KT-60KP	1x2mm	Kevlar+Polyester	1.2mm	500g / m <sup>2</sup>	-70 ~ 320 °C	4000mm	900/600N/cm
KT-24K	2x2mm	Kevlar	1.2mm	500g / m <sup>2</sup>	-70 ~ 320 °C	4000mm	900/600N/cm